















d-COLOR

MF2613en/2614en

Perfect multifunctional systems for small workgroups, the d-Color MF2613en and MF2614en A4 colour systems are the answer to users looking for **compact** office devices delivering **high performance**. The automatic duplex for both print and scan function speeds up workflows, while the four paper-input channels (bypass and three trays*) guarantee complete **flexibility** for document production on all paper formats.

Robust, with long-life components, the d-Color MF2613en and MF2614en ensure operating continuity in the office and keep running costs to a minimum. As environmental friendly devices, the systems feature a low-energy white LED scanner bar to copy and scan, and eco-friendly packaging made from recycled materials.

ENGINE SPEED 26 PPM IN COLOUR AND B/W
PRINTER, COPIER, COLOUR SCANNER
AND FAX (MF2614en ONLY)
STANDARD 35 opm DUPLEX DOCUMENT FEED
PAPER WEIGHT UP TO 220 g/m²
PRINT QUALITY UP TO 9600 dpi
COMPATIBILITY WITH A VARIETY
OF ID CARD READERS
SSL, IPSEC, SNMPv3 AND PRIVATE PRINTING
SECURITY STANDARDS
HIGHLY COMPETITIVE PRINTING COSTS



*Configuration with 2 additional optional trays

AIRPRINT® COMPATIBILITY



Duplex, copying, scanning



Paper capacity (max. 1,300 sheets)



USB interface

TECHNICAL SPECIFICATIONS

GENERAL	
Туре	Desktop
Technology	Colour laser
Operator panel	5-line LCD display
RAM memory	1,024 MB standard, max. 2,048 MB
Interfaces	USB 2.0 (Hi-Speed), USB Host, Fast Ethernet interfaces
	10/100Base-TX/1000Base-T, slot for optional
	CompactFlash, slot for optional print server
Warm-up time	Approximately 29 seconds or less after power-on
Accounting	20 department codes
Monthly duty cycle	Max. 65,000 pages
Power requirements	220-240V, 50/60 Hz
Power consumption	Print mode: 426W (MF2613 ^{en}), 427W (MF2614 ^{en})
	Copy mode: 444W (MF2613 ^{en}), 445W (MF2614 ^{en})
	Stand-by: 73W (MF2613 ^{en}), 76W (MF2614 ^{en})
	Idle: 3.22W (MF2613 ^{en}), 3.47W (MF2614 ^{en})
Noise level (ISO 7779/ISO 9296)	Print/copy: 48.3 (MF2613 ^{en}), 48.5 (MF2614 ^{en}) dB(A)
	Stand-by: 30 dB(A)
Dimensions (WxDxH)	514 x 550 x 580 mm
Weight	Approximately 36.5 kg (including consumables)
Consumables (ISO/IEC 19798)	Initial toner cartridge: up to 3,500 black pages,
	up to 2,500 CMY pages
	Toner: up to 7,000 black pages, up to 5,000 CMY pages

PRINTER	
Speed	Up to 26 ppm b/w and colour
First print out	Approximately 9 seconds b/w, 10.5 seconds colour
Processor speed	PowerPC 464 / 667 MHz
Resolution	600 x 600 dpi, multibit up to 9,600 x 600 dpi
Emulations	PCL 6 (5c/XL), KPDL 3 (compatible with PostScript 3), PDF Direct Print, PDF/A, PDF ver. 1.5, XPS Direct Print
Operating systems	All current Windows operating systems, MAC OS X 10.4 or higher, Unix, Linux
Fonts	93 scalable (PCL6, KPDL3) + 8 (Windows Vista), 1 bitmap, 45 one-dimensional barcodes and 1 two-dimensional barcode (PDF417)
Functions	Direct printing of encrypted PDFs, IPP printing, e-mail printing, WSD printing, secure printing via SSL/IPsec/SNMPv3, private printing (with additional memory), AirPrint® compatibility

SCANNER	
Document input	RADF, flatbed
Speed	Up to 35 ipm (300 dpi, A4, b/w), up to 25 ipm (600 dpi, A4, b/w - 300 dpi, A4, colour)
Resolution	600, 400, 300, 200 dpi (256-levels greyscale per colour)
Scan modes	Network TWAIN, WSD (WIA), Scan-to-Email/FTP/SMB/USB
Scan formats	Max. A4, Legal
File formats	TIFF, PDF, JPEG, XPS, PDF/A
Interfaces	Fast Ethernet 10/100Base-TX, USB Host 2.0
Functions	Integrated address book, Active Directory support, encrypted data transfer, simultaneous multiple transmission (e-mail, fax, SMB/FTP folder, print)

ITU-T Super G3
33.6 Kbps
< 3 seconds per page
MH, MR, MMR, JBIG
256 pages or more
Normal: 8 dots/mm x 3.85 lines/mm
Fine: 8 dots/mm x 7.7 lines/mm
Superfine: 8 dots/mm x 15.4 lines/mm
Ultrafine: 16 dots/mm x 15.4 lines/mm
Half-tones: 256-levels greyscale
22 destinations
100 entries
Network fax, duplex/encrypted transmission and reception,
polling, broadcast

COPIER	
Speed	Up to 26 cpm b/w and colour
First copy out	Approximately 10 seconds b/w, 12 seconds colour
Resolution	600 x 600 dpi
Greyscale	256 levels
Zoom	25% - 400% (1% increments)
Multicopy	1-999
Exposure modes	Manual/automatic, 7 levels
Functions	One scan many copies, electronic sorting, 2in1, 4in1, ID card copy, job booking, priority print, program recall job, automatic duplex, split copy, continuous scanning, automatic tray selection, copy density control

PAPER HANDLING	
Paper tray	250 sheets Paper formats: A6-A4, custom sizes
	(from 105 x 148 to 216 x 356 mm) Paper weight: 60-163 g/m²
Multi-purpose tray	50 sheets Paper formats: A6-A4, custom sizes (from 70 x 138 to 216 x 356 mm) Paper weight: 60-220 g/m²
Output paper capacity	150 sheets, face down
Automatic duplex	Standard
	Paper formats: A5-A4
	Paper weight: 60-163 g/m ²
Automatic Document Feeder	Paper formats: A5-A4, custom sizes
	(from 140 x 210 to 216 x 356 mm)
	Paper weight: 50-120 g/m ² simplex, 50-110 g/m ² duplex

OPTIONS	
Paper trays	Max. 2 trays (optional)
. ,	PF-520: 500 sheets, A4-A5, 60-163 g/m ²
	PF-530: 500 sheets, A4-A5, 60-220 g/m ²
Memory	512 MB and 1024 MB memory expansions
Hard disk	HD-6 (32 GB)
	HD-7 (128 GB)
ThinPrint support	IB-50, IB-51, UG-33
Table	
IC card reader	
IC card reader holder	
Compact flash card	

Performance refers to use of product in optimal conditions. With the right to change technical specifications. The registered trademarks are property of their respective owners. The d-Color MF2613 $^{\rm en}$ and MF2614 $^{\rm en}$ are distributed by Olivetti S.p.A. (04/14) Code: 29178-00

OLIVETTI S.P.A. VIA JERVIS 77 10015 IVREA (TO) ITALIA www.olivetti.it





